

TABLES OF AMERICAN STANDARDS (AS SERIES)

AS-0XX Size : Cross-section W = 1.78 mm							
AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm
-001*	0.74	-016	15.60	-031	44.17	-046	107.67
-002*	1.07	-017	17.17	-032	47.35	-047	114.02
-003*	1.42	-018	18.77	-033	50.52	-048	120.37
-004	1.78	-019	20.35	-034	53.70	-049	126.72
-005	2.57	-020	21.95	-035	56.87	-050	133.07
-006	2.90	-021	23.52	-036	60.05		
-007	3.68	-022	25.12	-037	63.22		
-008	4.47	-023	26.70	-038	66.40		
-009	5.28	-024	28.30	-039	69.57		
-010	6.07	-025	29.87	-040	72.75		
-011	7.65	-026	31.47	-041	75.92		
-012	9.25	-027	33.05	-042	82.27		
-013	10.82	-028	34.65	-043	88.62		
-014	12.42	-029	37.82	-044	94.97		
-015	14.00	-030	41.00	-045	101.32		

*Please note : for AS-001 cross-section W = 1.02 mm
for AS-002 cross-section W = 1.27 mm
for AS-003 cross-section W = 1.52 mm

AS-1XX Size : Cross-section W = 2.62 mm							
AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm
-102	1.24	-112	12.37	-122	28.24	-132	44.12
-103	2.06	-113	13.94	-123	29.82	-133	45.69
-104	2.84	-114	15.54	-124	31.42	-134	47.29
-105	3.63	-115	17.12	-125	32.99	-135	48.90
-106	4.42	-116	18.72	-126	34.59	-136	50.47
-107	5.23	-117	20.29	-127	36.17	-137	52.07
-108	6.02	-118	21.89	-128	37.77	-138	53.64
-109	7.59	-119	23.47	-129	39.34	-139	55.25
-110	9.19	-120	25.07	-130	40.94	-140	56.82
-111	10.77	-121	26.64	-131	42.52	-141	58.42

AS-1XX Size : Cross-section W = 2.62 mm							
AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm
-142	59.99	-152	82.22	-162	145.72	-172	209.22
-143	61.60	-153	88.57	-163	152.07	-173	215.57
-144	63.17	-154	94.92	-164	158.42	-174	221.92
-145	64.77	-155	101.27	-165	164.77	-175	228.27
-146	66.34	-156	107.62	-166	171.12	-176	234.62
-147	67.95	-157	113.97	-167	177.47	-177	240.97
-148	69.52	-158	120.32	-168	183.82	-178	247.32
-149	71.12	-159	126.67	-169	190.17		
-150	72.69	-160	133.02	-170	196.52		
-151	75.87	-161	139.37	-171	202.87		

AS-2XX Size : Cross-section W = 3.53 mm							
AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm
-201	4.34	-222	37.69	-243	104.37	-264	190.09
-202	5.94	-223	40.87	-244	107.54	-265	196.44
-203	7.52	-224	44.04	-245	110.72	-266	202.79
-204	9.12	-225	47.22	-246	113.89	-267	209.14
-205	10.69	-226	50.39	-247	117.07	-268	215.49
-206	12.29	-227	53.57	-248	120.24	-269	221.84
-207	13.87	-228	56.74	-249	123.42	-270	228.19
-208	15.47	-229	59.92	-250	126.59	-271	234.54
-209	17.04	-230	63.09	-251	129.77	-272	240.89
-210	18.64	-231	66.27	-252	132.94	-273	247.24
-211	20.22	-232	69.44	-253	136.12	-274	253.59
-212	21.82	-233	72.62	-254	139.29	-275	266.29
-213	23.39	-234	75.79	-255	142.47	-276	278.99
-214	24.99	-235	78.97	-256	145.64	-277	291.69
-215	26.57	-236	82.14	-257	148.82	-278	304.39
-216	28.17	-237	85.32	-258	151.99	-279	329.79
-217	29.74	-238	88.49	-259	158.34	-280	355.19
-218	31.34	-239	91.67	-260	164.69	-281	380.59
-219	32.92	-240	94.84	-261	171.04	-282	405.26
-220	34.52	-241	98.02	-262	177.39	-283	430.66
-221	36.09	-242	101.19	-263	183.74	-284	456.06

AS-XXX SERIES

AS-3XX Size : Cross-section W = 5.33 mm							
AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm
-309	10.46	-334	66.04	-359	145.42	-384	380.37
-310	12.07	-335	69.22	-360	148.59	-385	405.26
-311	13.64	-336	72.39	-361	151.77	-386	430.66
-312	15.24	-337	75.57	-362	158.12	-387	456.06
-313	16.81	-338	78.74	-363	164.47	-388	481.41
-314	18.42	-339	81.92	-364	170.82	-389	506.81
-315	19.99	-340	85.09	-365	177.17	-390	532.21
-316	21.59	-341	88.27	-366	183.52	-391	557.61
-317	23.16	-342	91.44	-367	189.87	-392	582.68
-318	24.77	-343	94.62	-368	196.22	-393	608.08
-319	26.34	-344	97.79	-369	202.57	-394	633.48
-320	27.94	-345	100.97	-370	208.92	-395	658.88
-321	29.51	-346	104.14	-371	215.27		
-322	31.12	-347	107.32	-372	221.62		
-323	32.69	-348	110.49	-373	227.97		
-324	34.29	-349	113.67	-374	234.32		
-325	37.47	-350	116.84	-375	240.67		
-326	40.64	-351	120.02	-376	247.02		
-327	43.82	-352	123.19	-377	253.37		
-328	46.99	-353	126.37	-378	266.07		
-329	50.17	-354	129.54	-379	278.77		
-330	53.34	-355	132.72	-380	291.47		
-331	56.52	-356	135.89	-381	304.17		
-332	59.69	-357	139.07	-382	329.57		
-333	62.87	-358	142.24	-383	354.97		

AS-XXX SERIES

AS-4XX Size : Cross-section W = 6.99 mm					
AS Nr.	ID. mm	AS Nr.	ID. mm	AS Nr.	ID. mm
-425	113.67	-447A	234.90	-467	481.46
-426	116.84	-448	240.67	-468	494.16
-427	120.02	-448A	247.65	-469	506.86
-428	123.19	-449	253.37	-470	532.26
-429	126.37	-449A	260.35	-471	557.66
-430	129.54	-450	266.07	-472	582.68
-431	132.72	-450A	273.05	-473	608.08
-432	135.89	-451	278.77	-474	633.48
-433	139.07	-451A	285.75	-475	658.88
-434	142.24	-452	291.47		
-435	145.42	-452A	298.45		
-436	148.59	-453	304.17		
-437	151.77	-454	316.87		
-438	158.12	-455	329.57		
-439	164.47	-456	342.27		
-440	170.82	-457	354.97		
-441	177.17	-458	367.67		
-442	183.52	-459	380.37		
-443	189.87	-460	393.07		
-444	196.22	-461	405.26		
-445	202.57	-462	417.96		
-445A	209.55	-463	430.66		
-446	215.27	-464	443.36		
-446A	222.25	-465	456.06		
-447	227.97	-466	468.76		